

TRACE

ACCENT LIGHT LUMINAIRE

STL22465BR/30



7W

Power

420lm

Luminous flux

40°

Beam angle




TECHNICAL SPECIFICATIONS TABLE

Beam angle	40°
Luminous efficacy	60lm/W
Power factor	0,4
Luminous flux	420lm
Frequency	50/60Hz
CRI (Color rendering index)	>93(R9 >60)
Power	7W
Correlated color temperature (CCT)	3000K
Voltage (Vac)	100-240Vac
Lifespan (L70)	25000h

Technical Drawing

STL22465




Graphics

STL22465BR

1m	85lx	0,8m
2m	213lx	1,6m
3m	95lx	2,4m
4m	53lx	3,2m
5m	34lx	4m

h, Emax, Ø

STL22465BR



OTHER INFORMATION

Finishing	White
Color temperature	Warm white
Dimmable	No
Warranty	2 years
Patent information	Patented product
Prevailing material	Aluminum

DOWNLOADS

[↓ IES FILE - STL22465BR/30](#)[↓ MANUAL Trace](#)[↓ SKETCHUP - STELLA - STL22465BR-30 - STL22465PTO-30 - TRACE_PACK.zip](#)[↓ REVIT - STL22465BR_30_STL22465PTO_30.rfa](#)