

TRACE

ACCENT LIGHT LUMINAIRE

STL22465PTO/30



7W

Power

420lm

Luminous flux

40°

Beam angle




TECHNICAL SPECIFICATIONS TABLE

Beam angle	40°
Luminous efficacy	60lm/W
Power factor	0,4
Luminous flux	420lm
Frequency	50/60Hz
CRI (Color rendering index)	>93(R9 >60)
Power	7W
Correlated color temperature (CCT)	3000K
Voltage (Vac)	100-240Vac
Lifespan (L70)	25000h

Technical Drawing

STL22465




Graphics

STL22465PTO/30

1m	887lx	0,8m
2m	222lx	1,6m
3m	99lx	2,4m
4m	55lx	3,2m
5m	35lx	4,1m

Altura, Emax e Diâmetro

STL22465PTO/30



— C0/180 — C90/270

OTHER INFORMATION

Finishing	Black
Color temperature	Warm white
Dimmable	No
Warranty	2 years
Patent information	Patented product
Prevailing material	Aluminum

DOWNLOADS

[↓ IES FILE - STL22465PTO/30](#)[↓ MANUAL Trace](#)[↓ SKETCHUP - STL22465BR_30_STL22465PTO_30.skp](#)[↓ REVIT - STL22465BR_30_STL22465PTO_30.rfa](#)