

TRACE

ACCENT LIGHT LUMINAIRE

STL22466PTO/30



14W

Power

840lm

Luminous flux



40°

Beam angle

TECHNICAL SPECIFICATIONS TABLE

Beam angle	40°
Luminous efficacy	60lm/W
Power factor	0,4
Luminous flux	840lm
Frequency	50/60Hz
CRI (Color rendering index)	>93(R9 >60)
Power	14W
Correlated color temperature (CCT)	3000K
Voltage (Vac)	100-240Vac
Lifespan (L70)	25000h

Technical Drawing

STL22466




Graphics

STL22466PTO/30

1m	1628lx	0,8m
2m	407lx	1,6m
3m	181lx	2,4m
4m	102lx	3,2m
5m	65lx	4m

Altura, Emax e Diâmetro

STL22466PTO/30



C0/180 C90/270

OTHER INFORMATION

Finishing	Black
Color temperature	Warm white
Dimmable	No
Warranty	2 years
Patent information	Patented product
Prevailing material	Aluminum

DOWNLOADS

[↓ IES FILE - STL22466PTO/30](#)[↓ MANUAL Trace](#)[↓ SKETCHUP - STL22466BR_30_STL22466PTO_30.skp](#)[↓ REVIT - STL22466BR_30_STL22466PTO_30.rfa](#)